











Please find information on IP symbols on our info sheet or at www.ortlieb.com/ip-symbols



Carrying handle for mounting and releasing the QL2.1 system

Carrying strap Base feet

Automatically closing 16mm QL2.1 hooks

Exchangeable hook inserts with antiscratch function (8, 10, 12 mm)

Adjustable and rotatable mounting hook (in 15° steps) with anti-scratch function Semi-elliptical hook rail made of two-component synthetic with anti-scratch function reduces

abrasions on rack

Abrasion protection

Height cm/in. Width cm/in. 40/15,7 25/9,8

Lid closure with dust flap underneath

Two lateral 3M Scotchlite reflectors

Depth cm/in. Vol. l/cu.in. 14/5,5 30/1831 (pair)

Weight g/oz. 1680/59.3 (pair)

Edge protector with slots for mounting the ORTLIEB carrying system

- · Universal panniers for low-rider racks in the front or rear racks
- · Abrasion restistant Cordura fabric
- · QL2.1 mounting system for racks with max. 16 mm tube diameter
- · 20 mm hook available as separate accessory (e.g. for E-bikes)
- · Reduction inserts for tube diameters 8, 10 und 12 mm with anti-scratch function preventing abrasion on the rack
- · Hooks adjustable without requiring tools
- · Lower hook rail made of two-component hard-soft synthetic with anti-scratch function protecting the rack
- · Including integrated inner pocket and shoulder strap
- · Ideal alternative to Front-Rollers (can be loaded higher due to its lids)
- · Ideal as "small" rear panniers for children's or youth bikes
- · Simultaneous use of ORTLIEB Travel-Biker or Trunk-Bag possible
- · Possibility to attach the ORTLIEB carrying system
- · Highly reflective Scotchlite reflector
- · Easy to clean inside

Optional accessories: ORTLIEB carrying system, outer pocket/s (size S), mesh pocket, bottle cage, 20 mm QL2.1 hook, anti-theft device long

Panniers comes with shoulder strap, reduction inserts 8, 10 and 12 mm (2 pairs per size)

Note: In order to meet standard IP54 (5=protected against dust, 4=protected against splash water coming from all directions) the lid must be properly closed.

WODNG1-INFO

nlue\_0.1 20.15